

# Aurora454

Outdoor gNB Datasheet

**Baicells**  
Connect More with Less



## INTRODUCTION

The Baicells Aurora 454 is an advanced outdoor 5G Sub-6G integrated base station (gNB), which is designed and developed based on 5G SoC solution. This 4x60 watts gNB is low power consumption, subminiature and easy to maintenance.

This product helps operators to enhance the coverage performance of 5G networks effectively, improve the capacity of 5G networks and eliminate the blind district, meanwhile it also can help to reduce the system power consumption.

This product comes with a standard one-year warranty; an extended warranty is also available.

## HIGHLIGHTS

*NOTE: Features can vary based on model or region.*

- Standard NR FR1 Bands n41
- Comply with 3GPP Release 15 and Release 16
- GUI-based local and remote Web management
- Supports 100MHz bandwidth
- Peak rate: Up to DL 1500Mbps and UL 660Mbps
- Supports up to 1200 users
- Supports Stand Alone (SA) mode
- Supports F1 setting\*
- Supports SCTP control (IKE SCTP)
- Supports embedded 5G core (HaloB)
- Integrated small cell form factor for quick and easy installation
- Supports flexible xHaul
- Highly secured with equipment certification against potential intrusion risk
- Supports TR-069 network management interface
- Lower power consumption, which reduces OPEX, can be powered easily by Baicells compact outdoor smart UPS

\* Planned for future release

## TECHNOLOGY

|                         |   |
|-------------------------|---|
| Standard                | 5G NR TDD (3GPP R15 and R16 compliant)  |
| TDD UL/DL Configuration | 5ms periodicity ( $\mu=1$ ): DDDDD+DDSUU<br>5ms periodicity ( $\mu=1$ ): DDDDD+SUUUU*<br>2.5ms dual periodicity ( $\mu=1$ ): DDDSU+DDSUU<br>2.5ms single periodicity ( $\mu=1$ ): DDDSU*, DSUUU |
| Frequency Band          | n41 (2496 MHz – 2690MHz)  |
| Channel Bandwidth       | n41: 20/30/100MHz   |
| Multiplexing            | 4x4 MIMO (DL: 4L, UL: 4L)   |
| Security                | Radio: SNOW 3G/AES-128<br>Backhaul: IPsec (X.509 AES-128, AES-256, SHA-128, SHA-256)  |

\* Planned for future release

## INTERFACE

|                    |   |
|--------------------|---|
| Ethernet Interface | 1 x 2.5GE RJ-45<br>3 x 10GE optical interface (SFP+)                          |
| Power Supply       | -40VDC ~ -57VDC, nominal -48VDC   |
| Protocols Used     | IPv4/IPv6, UDP, TCP, ICMP, NTP, SSH, IPsec, TR-069, HTTP/HTTPs, DHCP          |
| Network Management | IPv4/IPv6, HTTP/HTTPs, TR-069, SSH, Embedded 5GC*                             |
| VLAN/VxLAN         | 802.IQ/VxLAN  |
| LED Indicators     | 5 x status LED<br>RUN/ACT/ALM/BH/FB   |
| RF Antenna         | 4T4R external high gain antenna with N-Type connectors, or integrated antenna |
| GPS Antenna        | External GPS antenna, N-Type connector  |

\* Planned for future release

## PERFORMANCE

| Peak Data Rate                               | 100 MHz   |                          |
|--|-----------|--------------------------|
|  | DL (Mbps) | UL (Mbps)<br>with 256QAM |
| 5ms periodicity (DDDDD+DDSUU, 6:4:4)         | 850       | 230                      |
| 5ms periodicity (DDDDD+SUUUU, 6:4:4)*        | 525       | 400                      |
| 2.5ms dual periodicity (DDDSU+DDSUU, 10:2:2) | 720       | 330                      |

|                          |  |     |     |
|--------------------------|--|-----|-----|
|                          | 2.5ms single periodicity (DDDSU, 10:2:2)*                                      | 850 | 230 |
|                          | 2.5ms single periodicity (DSUUU, 10:2:2)                                       | 380 | 660 |
| User Capacity            | Up to 1200 users   |     |     |
| Maximum Deployment Range | 5km  |     |     |
| Latency                  | Round-trip delay (RTD) less than 10 milliseconds                               |     |     |
| Receive Sensitivity      | -95 dBm (per channel)  |     |     |
| Modulation               | UL: MCS0 (QPSK) to MCS27 (256QAM)<br>DL: MCS0 (QPSK) to MCS27 (256QAM)         |     |     |
| Transmit Power Range     | 38dBm to 47.78 dBm per channel (combined +49dBm, configurable) (1 dB interval) |     |     |
| Quality of Service       | Complied with 3GPP standard 5G QoS Identifier (5QI)                            |     |     |
| ARQ/HARQ                 | Supported  |     |     |
| Synchronization          | GPS  |     |     |

\* Planned for future release

## FEATURES

|                 |  |
|-----------------|--|
| Voice           | VoNR/EPS-FB  |
| SON*            | Self-Organizing Network <ul style="list-style-type: none"> <li>Automatic Neighbor Relation (ANR)</li> <li>PCI confliction detection</li> </ul>   |
| Traffic Offload | Local breakout   |
| Maintenance     | <ul style="list-style-type: none"> <li>Local/Remote Web maintenance</li> <li>Online status management</li> <li>Performance statistics</li> <li>Fault management</li> <li>Local/Remote software upgrade</li> <li>Logging</li> <li>Connectivity diagnosis</li> <li>Auto startup</li> </ul> |

## LINK BUDGET

|      |                  |
|------|------------------|
| VSWR | <=1.5            |
| EIRP | Antenna gain = G |

|               |  |
|---------------|--|
|               | EIRP = (50.78+G)dBm/100MHz   |
| Power Control | UL Open-loop/Closed-loop Power Control, DL Power Allocation (3GPP TS 38.213 compliant) |

## PHYSICAL

|                           |   |
|---------------------------|---|
| Surge Suppression         | Power interface: Differential mode: 2 KA; Common mode: 4 KA     |
| Lightning Protection      | Power interface: Differential mode: ±10 KA; Common mode: ±20 KA |
| MTBF                      | ≥ 150000 hours  |
| MTTR                      | ≤ 1 hour  |
| Ingress Protection Rating | IP66  |
| Operating Temperature     | -40°F to 131°F / -40°C to 55°C                                  |
| Storage Temperature       | -58°F to 149°F / -50°C to 65°C                                  |
| Humidity                  | 5% to 95% RH  |
| Atmospheric Pressure      | 70 kPa to 106 kPa   |
| Power Consumption         | Maximum 650W  |
| Weight                    | 18kg  |
| Dimensions (HxWxD)        | 527 X 308X 120 millimeters                                      |
| Installation              | Pole or wall mount  |

## MODEL NUMBERS

|             |  |
|-------------|--|
| BSQ7041A454 | Aurora452outdoor 5G NR integrated TDD gNB<br>-n41(2496MHz-2690MHz),4T4R,4*60W, -48VDC, external antenna,<br>1*(2.5G)RJ45+3*(10GE)OPT |
|-------------|--|

NOTE: Customized versions can be requested. (AC version will be ready in the future)