

DATASHEET

CS-F12PAR / CS-F12PAW

DS-Control: 2-0-2 / 251201

1/2" Aluminum Plenum Rated Coax

CS-F12PAR / CS-F12PAW

Air Dielectric Coax, Aluminum Plenum Rated, Red & White Jacket, UL



Electrical Specifications

Product Model	CS-F12PAR500 (Red Jacket) CS-F12PAW500 (White Jacket)	CS-F12PAR (Red Jacket) CS-F12PAW (White Jacket)
Spool size	500ft/spool	1000ft/spool
Frequency (MHz)		DC-6000
Impedance (ohm)		50.0 ± 2.0
Capacitance		75.45 (pF/m), 23.0 (pF/ft)
Inductance		0.19(μH/m), 0.058 (μH/ft)
Propagation Velocity (%)		88
DC Breakdown Voltage (kV)		4.0
Insulation Resistance (MΩ)		> 10,000
Peak Power Rating (kW)		40.0
Cut-off Frequency (GHz)		8.8
VSWR. typical	555-2200MHz 2300-2700MHz 3300-4200MHz 4400-6000MHz	1.15 1.20 1.25 1.30

Mechanical Specifications

Diameter Over Inner Conductor (in/mm)	0.189 / 4.80
Diameter Over Insulation (in/mm)	0.461 / 11.70
Diameter Over Outer Conductor (in/mm)	0.545 / 13.85
Diameter Over Jacket (in/mm)	0.618 / 15.70
Minimum Bending Radius-Single (in/mm)	2.5 / 63.5
Minimum Bending Radius-Multiple (in/mm)	5.0 / 127
Maximum Tensile Force (N / lbf)	776 / 175
Cable Weight. lb./ft (kg/m)	0.13 (0.19)
Shipping Dimension (in/mm)	500ft Spool 21.7x 21.7x16.8 / 550x550x426 1,000ft Spool 28.3x28.3x15.5 / 720x720x394
Shipping Weight(lb./kg)	500ft Spool 90.4 / 41 1,000ft Spool 167.6 / 76

Environment

Application	Indoor / Outdoor
Storage Temperature	-25°C to +70°C
Operating Temperature	-25°C to +70°C
Installation Temperature	-20°C to +60°C

Attenuation

Frequency (MHz)	Attenuation (dB/100m)	Attenuation (dB/100ft)	Frequency (MHz)	Attenuation (dB/100m)	Attenuation (dB/100ft)
50	1.82	0.55	2100	12.54	3.82
100	2.29	0.70	2200	12.91	3.93
150	2.75	0.84	2300	13.27	4.04
174	2.96	0.90	2400	13.62	4.15
300	3.99	1.22	2500	13.98	4.26
340	4.29	1.31	2600	14.32	4.37
400	4.73	1.44	2700	14.67	4.47
450	5.07	1.55	2800	15.01	4.57
500	5.40	1.65	2900	15.34	4.68
600	6.02	1.83	3000	15.67	4.78
617	6.12	1.87	3100	16.00	4.88
698	6.58	2.01	3200	16.32	4.97
800	7.13	2.17	3300	16.64	5.07
894	7.61	2.32	3550	17.41	5.31
960	7.93	2.42	3600	17.56	5.35
1000	8.12	2.47	3700	17.86	5.44
1200	9.02	2.75	3800	18.16	5.53
1400	9.86	3.00	3900	18.45	5.62
1500	10.26	3.13	4000	18.74	5.71
1698	11.03	3.36	4100	19.04	5.80
1700	11.04	3.37	4200	19.33	5.89
1800	11.42	3.48	5000	21.68	6.61
1900	11.80	3.60	5500	23.16	7.06
2000	12.17	3.71	6000	24.42	7.44

Note: Typical attenuation at an ambient temperature +20°C (68°F)

Material

Inner Conductor	Copper Clad Aluminum Wire
Insulation	PE Spline
Outer Conductor	Ring Corrugated Aluminum
Jacket	PVC, Red & White Plenum Rated Jacket
Hanger Block	HB-F12D (dual, supports 3/8" or M10 threaded rod) HB-F12S (single, supports 3/8" or M10 threaded rod)
Prep Tool	AP-F12 (Prep-tool), FL-F12(Flaring tool), BL-F12 (Blades) TL-F12(Tool kit included AP-F12, FL-F12 and hard case)
Associated Connectors	CN-NM-F12: N-Male / CN-NF-F12: N-Female CN-4M-F12: 4.3-10-Male / CN-4F-F12: 4.3-10-Female

Compliance & Certification

Certification	Plenum Rated. CMP ETL UL-444/CSA C22.2NO214 FT6
RoHS	Compliant